## Assembly Instructions for the Connect+ Passenger Kit

#### Materials Needed

- 13mm open-end wrench
- Screwdriver
- M8 Bolts & Washers
- M5 Bolts
- Footpeg
- Passenger Seat

# Step-by-Step Instructions for Cafe Cruiser & Rift

#### Step 1: Install Foot Pegs

- 1. Slide a large washer onto the M8x35mm bolt.
- 2. Insert the bolt from the inside of the rear chainstay.
- 3. Carefully thread it into the foot peg, ensuring it only folds upward (not down or sideways).
- 4. Securely tighten with a 13mm wrench.
- 5. Repeat for the other side.

#### Step 2: Attach Wheel Covers

- 1. Slide a small washer onto each M5x15mm bolt.
- 2. Remove the protective film from one Wheel Cover.
- 3. Align the Wheel Cover against the rear frame and insert each bolt with a washer into the five slots.

#### Step 3: Install the Connect+ Seat

- 1. Place the seat on the rack with the slanted end facing forward.
- 2. Align the latch mechanism in the square section of the rack.
- 3. Pull the latch pin backward to retract the latch.
- 4. Press the seat down until the pin slides back forward and locks.
- 5. Do not force the latch.
- 6. Double-check that the seat is secure before riding.



# Step-by-Step Instructions for Portola

Most steps are the same as for Cafe Cruiser & Rift, with a few changes:

### Step 1: Attach the Foot Pegs

- 1. Use M8x20mm bolts instead of M8x35mm.
- 2. Slide a washer onto each bolt.
- 3. Insert the bolt from inside the rear braze-on (behind the axle).
- 4. Thread it into the foot peg, ensuring it only folds upward.
- 5. Tighten securely with a 13mm wrench.



Step 2: Install Connect+ Seat

- 1. Place the seat on the rack with the slanted end facing forward.
- 2. Align the latch mechanism in the square section of the rack.
- 3. Pull the latch pin backward to retract the latch.
- 4. Press the seat down until the pin slides back forward and locks.
- 5. Do not force the latch.
- 6. Double-check that the seat is secure before riding.

Note: Wheel covers are not needed for Portola.

# Final Steps & Review

- Ensure all bolts are tightened securely.
- Check hardware as part of regular bike maintenance.

For any questions or additional assistance, please contact customer support.